

MODEL COMPARISON

GPL 750

GPL 5000

GPL 10000

Appropriate Flow Conditions

Low, intermittent,
& no flow

low & high flow,
medium pressure

High-pressure,
high flow

Gases

Natural gas, RNG, biogas

Natural gas, RNG, biogas,
propane (LP)

Natural gas

Applications

Municipalities, small city
gate stations

Municipalities, small-large
city gate stations at low
pressure

Large city gate stations,
transmission lines

Odorant Injection Type

Batch

Batch

Continuous

Actuated by
[not actuated by pipeline gas]

Differential Pressure

Differential Pressure

Electric-powered dual
bellows pump

Zero Emissions



Odor Free Operation and Maintenance



Gas Pipeline Pressure

1 to 225 PSI

1 to 400 PSI

Up to 1480 PSI

Odorant Injection Min – Max Flow Rate
[@0.5 lbs./MMSCFH]

0-18 (std); 0-24 MMSCFD
(HC model)

0-512.8 MMSCFD

0.48-240 MMSCFD

Turndown Ratio

180,000:1

512:1

500:1

Operating Temp Range
[Heater assembly option for below 0°F]

0 to 120°F (-18 to 49°C)

0 to 120°F (-18 to 49°C)

0 to 140°F (-18 to 60°C)

Horner Controller 7" color touchscreen
[Optional: 4" and Spanish mode]



Tank Sizes

60, 120, 250 gal

60, 120, 250, 500, 1000
gal

60, 120, 250, 500, 1000
gal

Hazardous Area Class

CL I Div 2 Groups C & D
CL I Div 1 (optional)

CL I Div 2 Groups C & D
CL I Div 1 (optional)

CL I Div 2 Groups C & D

Design Configuration:

Odorizer Only



with tank and containment skid



with skid extension



Complete Systems

permanent



temporary or pickling



portable system (easy to move)



turnkey system (movable)

